



**CANTHERM DISTRIBUTORS
ARCOTHERM HEATERS**

JUMBO SERIES: SPECIFICATIONS

	JUMBO 700	JUMBO 900
HEAT INPUT - BTU	700,000	900,000
HEAT OUTPUT - BTU	595,000	765,000
HEATED AIRFLOW ó CFM	7420	8830
FUEL CONSUMPTION ó GPH	5.04	6.48
FUEL CONSUMPTION ó (NG) CFH	685	881
MIN. SUPPLY PRESSURE (NG)	min 7ö w. c. ó max 14ö w. c.	min 7ö w. c. ó max 14ö w. c
FUEL CONSUMPTION ó (LP) CFH	275	353
MIN. SUPPLY PRESSURE ó (LP)CF	min 8ö w. c. ó max 14ö w. c.	min 8ö w. c. ó max 14ö w. c
MAX AIR TEMPERATURE ó Fahrenheit	250	250
POWER SUPPLY	220 v	220 v
AMPS	7.8	10.3
FAN MOTOR POWER ó HP (RPM)	2 (1700)	3 (1700)
BURNER MOTOR POWER ó HP (RPM)	1/4 (3300)	¼ (3300)
MAX DUCT LENGTH ó 1 WAY	200 ft.	200 ft
MAX DUCT LENGTH ó 2 WAY	100 ft.	100 ft.
DIMENSIONS	77ö x 36ö x 53ö	88ö x 39ö x 59ö
WEIGHT ó LBS.	550	793